

RECEIVED  
CENTRAL FAX CENTER

SEP 30 2005

MARTIN & FERRARO, LLP  
1557 Lake O'Pines Street, NE  
Hartville, Ohio 44632

Telephone  
(330) 877-0700

Facsimile  
(330) 877-2030

FACSIMILE TRANSMITTAL

<b>TO:</b>	<b>FROM:</b>
<b>Name:</b> Mail Stop AMENDMENT Group Art Unit 3764/Examiner Michael Brown	<b>Name:</b> Thomas H. Martin, Esq.
<b>Firm:</b> U.S. Patent & Trademark Office	<b>Phone No.:</b> 330-877-2277
<b>Fax No.:</b> 571-273-4702	<b>No. of Pages (including this):</b> 111
<b>Subject:</b> U.S. Patent Application No. 08/480,908 Gary K. Michelson Filed: June 7, 1995 THREADED FRUSTO-CONICAL INTERBODY SPINAL FUSION IMPLANTS Attorney Docket No. 101.0053-00000 Customer No. 22882	<b>Date:</b> September 30, 2005  <b>Confirmation Copy to Follow:</b> NO

Message:

TRANSMISSION 3 OF 4

CERTIFICATE OF TRANSMISSION UNDER 37 CFR 1.8

I hereby certify that the attached Transmittal Form (in duplicate; \$1,020.00 total amount to cover the three-month extension fee is to be charged to Deposit Account No. 50-1068), Reply to Office Action, Declaration of Gary K. Michelson Under 37 C.F.R. § 1.131 with Exhibits A and B, and Declaration of Amedeo F. Ferraro with Exhibits A-H are being facsimile transmitted to the U.S. Patent and Trademark Office on September 30, 2005.



Todd M. Martin

If there is a problem with this transmission please call Sandy Blackmon at 330-877-1202 or the sender at the number above.

The information contained in this facsimile message is privileged and confidential information intended only for the use of the addressee listed above. If you are not the intended recipient or the employee or agent responsible to deliver this message to the intended recipient, please do not use this transmission in any way, but contact the sender by telephone.

EXHIBIT E

APPLICATION FOR LETTERS PATENT

BY

GARY KARLIN MICHELSON, M.D.

FOR

IMPROVED FRUSTO-CONICAL INTERBODY  
SPINAL FUSION IMPLANTS

CERTIFICATE OF EXPRESS MAILING

"Express Mail"

Mailing Label No. EG US

Date of Deposit: [REDACTED]

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to:

Signed:

PATENT APPLICATION  
Assistant Commissioner for Patents  
Washington, D.C. 20231.

Typed or  
Printer's Name: Sandra Mirreler

Date: [REDACTED]

CONICAL.AP4

1

## BACKGROUND OF THE INVENTION

### Related Applications

This application is a continuation in part of copending United States application Serial No. 08/396,414 filed on February 27, 1995 which is a continuation-in-part of United States application Serial No. 08/074,781 filed on June 10, 1993, which is a continuation in part of United States application Serial No. 07/698,674 filed on May 10, 1991 which is a divisional of application Serial No. 07/205,935 filed on June 13, 1988, now United States Patent No. 5,015,247 all of which are incorporated herein by reference.

This application is also a continuation-in-part of United States application Serial No. 08/390,131 entitled Interbody Spinal Fusion Implants filed on February 17, 1995.

### Field of the Invention

The present invention relates generally to interbody spinal fusion implants, and in particular to spinal fusion implants configured to restore and maintain two adjacent vertebrae of the spine in anatomical lordosis.

### Description of The Related Art

Interbody spinal fusion refers to the method of achieving bony bridging between adjacent vertebrae through the disc space, the space between adjacent vertebrae normally occupied by a spinal disc. Numerous implants to facilitate such a fusion have been described by Cloward, Brantigan, Michelson, and others, and are known to those skilled in the art. Generally, cylindrical implants offer the advantage of conforming to an easily prepared recipient bore spanning the disc space and penetrating into each of the adjacent vertebrae. Such a bore may be created by use of a drill.

It is an anatomical fact that both the cervical spine and the lumbar spine are normally lordotic, that is convex forward. Such alignment is important to the proper functioning of the spine. Commonly, those conditions which require treatment by spinal fusion are associated with a loss of lordosis.

Michelson in U.S. Patent Application Serial No. 08/396,414, entitled APPARATUS AND METHOD OF INSERTING SPINAL IMPLANTS teaches a method for restoring the anatomical lordosis of the spine while performing the interbody fusion procedure.

[REDACTED]

Therefore, there exists a need for spinal fusion implants and instrumentation that permits for the uniform depth of bone removal from each of the adjacent vertebrae while restoring anatomical lordosis.

#### SUMMARY OF THE INVENTION

The present invention is directed to a variety of interbody spinal fusion implants having at least a partially frusto-conical configuration and the instrumentation and methods by which the implants of the present invention can be utilized to achieve a desired anatomical lordosis of the spine.

In the preferred embodiment, the spinal fusion implants of the present invention have a body that is partially or fully frusto-conical in shape with an insertion end and a trailing end. The spinal fusion implants of the present invention may be further modified so that while the upper and lower surfaces are portions of a cone, at least one side portion may be truncated to form a planar surface that is parallel to the longitudinal axis of the implant to form straight walls. These implants may have a more tapered aspect at the small end of the cone to facilitate insertion. The spinal fusion implants of the present invention may be relatively solid or hollow and may have surface roughenings to promote bone ingrowth and stability. The spinal fusion implants of the present invention may have wells extending into the material of the implant from the surface for the purpose of holding fusion promoting materials and to provide for areas of bone ingrowth fixation. These wells, or holes may pass, either into or through the implant. The spinal

fusion implants of the present invention may have a hollow central chamber which may be in communication through various openings to the surface of the implant and such chamber may be capable of being closed with a cap or similar means. Still further, a variety of surface irregularities may be employed to increase implant stability and implant surface area, and/or for the purpose of advancing the spinal fusion implant into the fusion site. The exterior of the spinal fusion implant of the present invention may have wholly or in part, a rough finish, knurling, forward facing ratchetings, threads or other surface irregularities sufficient to achieve the purpose described. The spinal fusion implants of the present invention may be made of a mesh-like material, porous material, or any metal, plastic, ceramic or combination sufficient for the intended purpose. Such implants may be loaded with, composed of, or treated with materials to make them bioactive to the fusion process, and may be wholly or in part bioabsorbable.

The spinal fusion implants of the present invention offer significant advantages over the prior art implants:

1. Because the spinal fusion implants of the present invention are at least partially frusto-conical in shape and taper from the leading edge to the trailing edge, they are easy to introduce and easy to fully insert into the spinal segment to be fused.
2. As the spinal fusion implants of the present invention are generally implanted from the anterior to posterior aspect of the spine, the shape of the implants are consistent with the shape of the disc, which the implants at least in part replace. That is the front of the disc is normally taller than the back of the disc, which allows for normal lordosis. The implants of the present invention are similarly taller anteriorly than they are posteriorly.
3. The spinal fusion implants of the present invention allow for a minimal and uniform removal of bone from the vertebrae adjacent the disc space while still providing for an interbody

fusion in lordosis.

4. The spinal fusion implants of the present invention conform to a geometric shape, which shape is readily producible at the site of fusion, to receive said spinal fusion implants.

The spinal fusion implants of the present invention can be made of any material appropriate for human implantation and having the mechanical properties sufficient to be utilized for the intended purpose of spinal fusion, including various metals such as cobalt chrome, stainless steel or titanium including its alloys, various plastics including those which are bio-absorbable, and various ceramics. Further, the spinal fusion implants of the present invention may comprise, wholly or in part, materials capable of directly participating in the spinal fusion process, or coated with chemical substances such as bone morphogenic proteins for the purpose of stimulating fusion activity. The implants of the present invention may be wholly or in part bioabsorbable.

#### OBJECTS OF THE PRESENT INVENTION

It is an object of the present invention to provide a spinal implant that is easily inserted into the spine, having a tapered leading end;

It is another object of the present invention to provide a spinal implant that tapers in height from one end to the other consistent with the taper of a normal spinal disc;

It is yet another object of the present invention to provide a spinal implant that is capable of maintaining anatomic alignment and lordosis of two adjacent vertebrae during the spinal fusion process;

It is still another object of the present invention to provide a spinal implant that is self stabilizing within the spine;

It is yet another object of the present invention to provide a spinal implant that is capable of providing stability

CONICAL.AP4

of Figure 1 illustrating the surface configuration of the implant of Figure 1.

Figure 2 is a side elevational view of an alternative embodiment of the spinal fusion implant of the present invention having a body and an external thread that are both frusto-conical.

Figure 3 is a cross sectional view along line 3--3 of the implant of Figure 2.

Figure 4 is a side elevational view of an alternative embodiment of the spinal fusion implant of the present invention having a frusto-conical body and a surface configuration comprising ratchetings for engaging bone, with surface blasting, wells, and